



# iData K1S Android Keyboard/Touchcontrol Terminal

## Time-tested & cost-effective option

iData K1S is an ultra-rugged Android keyboard-type smart terminal, which is time-tested in many scenarios such as new retail business, warehouses, manufacturing plants, express and logistics, etc. It improves the working capacity without increasing your purchase cost. By adding a pistol grip, K1S is able to deal with high-frequency scanning in inventory process.

### Multifunctional to meet requirements of different scenes

Equipped with iData's self-developed scanning engine, K1S can easily scan damaged, dirty, DPM barcodes, etc. The breakthrough Wi-Fi roaming technology, as well as the 5G PA amplifier, enable a better network experience in complex environments.

### Battery life designed for 1.5 shifts

The 4400mAh large battery can be used for 12 hours, which can meet the needs of long shifts and reduce the loss caused by equipment downtime. The battery is detachable so that it can work continuously right after the battery replacement.

### Enterprise-level protection to reduce malfunction losses

IP65 makes the equipment waterproof, dustproof, rainproof and snowproof. It can work the sun and rain environments outdoors. The 1.5-meter anti-drop design enables users to mount the equipment on forklifts, shelves and other heights confidently. This device is designed to survive accident drops.



Store management



E-commerce shipment



Warehouse management



Inventory management

JMDL Computer Peripheral Equipment Trading  
+63 917 887 8153 | +63 977 762 6854  
info@jmdl-ph.com | sales@jmdl-ph.com  
www.jmdl-ph.com

# K1S Technical Specifications

## System Configuration

Processor	Octa-core 2.0GHz high-performance processor
Operating System	Android 9.0 (GMS) / Android 11.0 (GMS)
Memory (ROM + RAM)	32GB + 3GB (standard), 64GB + 4GB (optional)
SIM	Single SIM card
Expansion Slot	Micro SD card (up to 256GB)
Display Screen	4-inch, resolution: 800*480 pixels
Touch Screen	Industrial capacitive screen, support wet-hand operation/glove mode/multi-touch/gesture operation
Camera	13 megapixels of rear camera, support auto-focusing/PDAF
Flashlight	800mA flashlight
Keypad	26 keypads: front key*23, side scan key *2, side power key *1
Keyboard Backlight	White
Battery	3.8V lithium battery, with 4400mAh, detachable, backup-battery support (support on selected terminals)
Audio	Built-in microphone
Charging Method	Type-C charging and pin port charging
Reminder	Vibration reminder/LED reminder
Vibrating Motor	Built-in vibrating motor
Sensors	G-sensor/ Proximity sensor/Light sensor
Intercom Function (Optional)	Support one-button PTT calls

## Scanning Engine

Barcode Type	It can scan one-dimensional / two-dimensional barcodes
Scanning Accuracy	≥3.33mil
Scanning Angle	Pitch: ±60°; Skew: ±45°; Tilt: 360°
View Angle	Horizontal: 44.3°, Vertical: 28.4°, Diagonal: 51°
Motion Error Tolerance	8m/s

## Communication Transmission

WWAN (Network Frequency)	China & Eurasian version: 2G: 900/1800 3G: WCDMA: B1/B8 4G: FDD-LTE: B1/B3/B7/B8/B20, TDD-LTE: B34/B38/B40 American version: 2G: B2/B3/B5 3G: B1/B2/B4/B5, CDMA&EVDO: BC0/BC1 (The United States) 4G: B1/B2/B3/B4/B5/B7/B12/B17/B28A/B28B/B41
WWAN (Data Service)	GSM/GPRS/EDGE/CDMA/UMTS/HSPA/HSPA+/EVDO /WCDMA/TD-SCDMA/TDD-LTE/FDD-LTE
WLAN Function	Wi-Fi 802.11a/b/g/n/r/ac/i/k/v (2.4G + 5G dual-band Wi-Fi), support Wi-Fi 5G PA amplifier
Bluetooth	Bluetooth 5.0, support BLE
GPS	GPS

## Structure Parameter

Dimension (L*W*D)	168mm*71mm*26mm
Weight	270g (including the battery)

## Environmental Parameter

Working Temperature	-20°C - 60°C *Do not charge under low temperature conditions for the safety concerns
Storage Temperature	-40°C - 70°C (without the battery)
Humidity	0 - 95% (no moisture condensation)
Drop Specification	Multiple drops to concrete floor from the height of 1.5m
Roller Drop Specification	1000 times of roller drops from a height of 0.5 meter
Ingress Protection	IP65
ESD Protection	±15KV (air discharge), ±8KV (contact discharge)

## Communication Interface

USB Interface	Type-C (with headset function) *1
OTG Interface	Support

## NFC (Optional)

Working Frequency	13.56 MHz
Reading Distance	Within 30 mm
Communication Protocol	ISO14443A/14443B/15693

## Development Support

Programming Language	Java
Development API	iScan API (Scanning Development Kits), Device API (Device Management/Configuration Development Kits), Android Standard Interface
Development Tool	Eclipse/Android Studio

## Accessories (More details in accessories guide)

Standard Accessories	USB cable*1, power adapter*1, hand strap*1, device-back strap*1, battery*1
Optional Accessories	Single charging cradle, bottom charger, 4-slot charging cradle, 4-slot battery charging cradle, pistol grip, fanny pack, protective film

**Each product comes with a pack of practical and cost-effective accessories**

## USB Cable

Type-C to USB cable, 1m in length, support charging and data transmission



CHA-USBC-GNR

## Hand Strap


Wear on your wrist to carry the device, avoid accidental drops, and assure the safety of equipment



MNT-HS-GNR

## Device-back Strap

Attach on the device back to help you hold the device easily and firmly, avoid accidental drops



MNT-BS-K1

## Battery

4400mAh, detachable design.

ps: every product comes with 1 unit, you can purchase extra unit



CHA-BTRY-K1S-4400MA

## Power Adapter

Input voltage 100-240V, output 5V2A. Support plug types of China/Europe/UK/US/Australia, match with CHA-USBC-GNR

ps: you may have one of the power adapters



CHA-PWAD-  
GNR-5V2A-CN



CHA-PWAD-  
GNR-5V2A-EU



CHA-PWAD-  
GNR-5V2A-UK



CHA-PWAD-  
GNR-5V2A-US



CHA-PWAD-  
GNR-5V2A-AU

## Improve management efficiency of devices and operational level of enterprises

### Bottom Charger

Bottom charger for the main unit, support charging for 1 device. USB-A port, can connect with CHA-PWAD-GNR-5V2A-XX accessory



CHA-BTC-K1

### Battery

4400mAh, detachable design.

ps: every product comes with 1 unit, you can purchase extra unit



CHA-BTRY-K1-4400MA

### Single Charging Cradle

Support charging for 1 main unit. Support plug types of China/Europe/UK/US/Australia

ps: you may have one of the power adapters



CHA-CRD1S-K1

### 4-slot Charging Cradle

Support maximum charging of 4 main units at the same time.

Support plug types of China/Europe/UK/US/Australia

ps: you may have one of the power adapters



CHA-CRD4S-K1

### 4-slot Battery Charging Cradle

Support maximum charging of 4 batteries at the same time. Support plug types of China/Europe/UK/US/Australia

ps: you may have one of the power adapters



CHA-CRD4B-K1

## K1S Optional Accessories for Portability

Accessories Guide

**Improve device portability and comfort for users, boost working efficiency**

### Pistol Grip

Pistol grip for main unit. Execute barcode scanning by pressing the grip trigger. Only those main units with pin port on the back are compatible



MNT-PG-K1

### Fanny Pack

Used to carry main units and other accessories. Can be tied to the waist or used as a crossbody bag



MNT-FP-GNR

## K1S Optional Accessories for Protection

Accessories Guide

**Lower risks of malfunction during usage, extend lifespan of devices**

### Protective Film

Protective film for touchscreen. It can protect the screen from cracking or being scratched in case there's any accidental drops or impact during usage



PRT-PTF-K1